

Material Safety Data Sheet



(Premix)

1. Product Data (Identification of the substance or mixture and of the supplier)	
Trade Name	Tipco Premix
Chemical Name	Cold Mixed Asphalt
Use	Maintenance road or pavement
Manufacturer/Importer	Tipco Asphalt Public Company Limited
Address	118/1 Rama6 Rd, Phayathai, Phayathai, Bangkok 10400
Telephone Number	+66(0)2273-6000

2. Hazards Identification

GHS SYMBOL (S)


Factory

0-5537-1581-2 Ext. 360



WARNING! Causes skin irritation

NFPA Hazard Rating



Inhalation	Hydrogen Sulfide is highly flammable and toxic. This vapor
	can occur and accumulate in the upper part of the storage
	tank / truck bulk and any containers. Inhalation may cause
	the olfactory nerve become less sensitivity.
Skin	Contact with product may cause skin damage.
Eye contact	Heated material can cause thermal burn of the eyes or
	blinded.

Head Office : Tipco Tower 118/1 Rama 6 Rd. Phayathai, Phayathai Bangkok10400 Tel: +66 (0) 2273-6000, 0-2271-0205 Fax: +66 (0) 2273-6030, 0-2271-1601 www.tipcoasphalt.com

: 259 Moo 8, Soi Ard.12032 Mittrapap Rd. Naklang Soongnern District, Nakhon Ratchasima 30380 Tel: +66 (0) 4433-5495-9 Fax: +66 (0) 4433-5495-9 : 271 Moo 15 Phitsanulok-Bangragum Rd., Bangragum, Bangragum District Phitsanulok 65140 Tel: +66 (0) 5537-1461-2, 0-5537-1581-2 Fax: +66 (0) 5537-1461-2,

PCO

TIPCO ASPHALT PUBLIC COMPANY



Material Safety Data Sheet



(Premix)

3. Composition/Information on Ingredient	
Manufacturing Information	Mixtures of the various components of the emulsion asphalt
	(CMS-2h) with aggregate or aggregate and additive.
U.N. Number	Not applicable
CAS Number	Not applicable
Cancer Material	Not applicable
4. First Aid Measure	
Skin Contacting	- If contact with product, wash immediately with oil.
	- Remove contaminated clothing and shoes.
Eye Contacting	Flush eyes with plenty of water at least 15 minutes.
	If irritation persists, seek medical attention immediately.
Inhalation	If breathing vapors or fumes then irritation to the nose or
	throat Remove to fresh air. If symptoms persist, seek

	throat. Remove to fresh air. If symptoms persist, seek
	medical attention immediately. If breathing disorders /
	angina / malaise / vomiting or unresponsive, give artificial
	respiration with 100% oxygen before brought to the nearest
	hospital.
Ingestion	In normal condition of use, it's less likely to occur. If this
	happen, do not induce vomiting and seek medical attention
	immediately.

5. Fire-Fighting Measures	
Specific hazards arising from chemicals	- When the water lost to the flames. Rest material still will be
	able to burn. May have hazardous combustion products
	such as complicated compounds in solid phase and liquid
	phase which are suspended in air, carbon dioxide gas
	(fumes), and unknown organic / inorganic compounds.
Fire-fighting procedures	- Removing all persons who not involved from the vicinity of
	the incident .

Head Office : Tipco Tower 118/1 Rama 6 Rd. Phayathai, Phayathai Bangkok10400 Tel: +66 (0) 2273-6000, 0-2271-0205 Fax: +66 (0) 2273-6030, 0-2271-1601 www.tipcoasphalt.com Factory

: 259 Moo 8, Soi Ard.12032 Mittrapap Rd. Naklang Soongnern District, Nakhon Ratchasima 30380 Tel: +66 (0) 4433-5495-9 Fax: +66 (0) 4433-5495-9 : 271 Moo 15 Phitsanulok-Bangragum Rd., Bangragum, Bangragum District Phitsanulok 65140 Tel: +66 (0) 5537-1461-2, 0-5537-1581-2 Fax: +66 (0) 5537-1461-2, 0-5537-1581-2 Ext. 360



Factory

Material Safety Data Sheet



(Premix)

	- Use foam, water spray(fog), dry chemical, carbon dioxide
	and may be sand or soil for small fires.
Special Fire Precaution	- Do not use water jet.
	- Hazardous substances from burning such as complex
	compounds with suspend in the air, carbon monoxide and
	organic-inorganic compound.
	- Boil-over or violent eruption in the presence of water.
Protective measures for fire fighters	Should wear appropriate protection equipment such as
	glove, firefighting suite, chemical, breathing apparatus.

6. Accidental Release Measures	
Personal precaution and Method for containment	Avoid skin contact, eyes contact and cloth contaminating.
	Don't inhale fumes or vapors. Move or eliminate all ignition
	sources around spillage area with well ventilation thorough
	the contaminated area.
Land Spill	Stop leaks or spreads with sand or soil and shovel into
	suitable containers and identify clearly in order to eliminate
	or rehabilitation by local law.
Water Spill	- Use sand, soil or other appropriate barricade to prevent
	entry into waterways, sewers, basements / confined areas or
	public water supply.
	- Alert the relevant authorities when materials entry into
	public water supply and scoop materials out of the water or
	absorb with appropriate absorbent.

7. Handling and Storage	
Storage Temperature	Store at ambient temperature and less than $100^\circ C$
Transport Temperature	Ambient temperature
Loading/ Unloading Temperature	Ambient temperature
Material and Coating Suitable	Container should be made from plastic bag or PE as
	resistant the sun, sticky and strong.

Head Office : Tipco Tower 118/1 Rama 6 Rd. Phayathai, Phayathai Bangkok10400 Tel: +66 (0) 2273-6000, 0-2271-0205 Fax: +66 (0) 2273-6030, 0-2271-1601 www.tipcoasphalt.com

259 Moo 8, Soi Ard. 12032 Mittrapap Rd. Naklang Soongnern District, Nakhon Ratchasima 30380 Tel: +66 (0) 4433-5495-9 Fax: +66 (0) 4433-5495-9
 271 Moo 15 Phitsanulok-Bangragum Rd., Bangragum, Bangragum District Phitsanulok 65140 Tel: +66 (0) 5537-1461-2, 0-5537-1581-2 Fax: +66 (0) 5537-1461-2,

0-5537-1581-2 Ext. 360

TIPCO ASPHALT

TIPCO ASPHALT PUBLIC COMPANY

Material Safety Data Sheet



(Premix)

Storage/ Handling	Keep in specific area with adequate ventilation at ambient
	temp. Label clearly and close the cover tightly. Avoid store
	near heat sources.

8. Exposure Controls/Personal Protect	tion
SN44	Wear appropriate gloves with international standard
Hand Protection	certificate which can protect hazards from chemicals and
	can resist heat such as PVC or Nitrile gloves, and should
	replace the gloves once deteriorated.
	If can't control concentrate of substance in air at level of
Respiratory Protection	safety acceptable, use respiratory protection equipment that
	suitable for working.
	Wear appropriate clothing and protective equipment such
Skin and Body Protection	as gloves, boot, and apron that can be protected heat and
	chemicals.
	Wear goggle /glasses / face shield If possible to spill.
Eyes Protection	

9. Physical and Chemical data	
Boiling Point (°C)	Not applicable
Melting Point (°C)	Not applicable
Vapor Pressure	Not applicable
Solubility	Insoluble
Density	Not applicable
Appearance Color and Odor	Solid, dark brown to black color, Petroleum odor.
pH-Value	Not applicable

10. Stability and reactivity	
Flash Point	Not applicable
Flammable limits	
- LEL %	Not applicable

 Head Office
 : Tipco Tower 118/1 Rama 6 Rd. Phayathai, Phayathai Bangkok10400 Tel: +66 (0) 2273-6000, 0-2271-0205 Fax: +66 (0) 2273-6030, 0-2271-1601 www.tipcoasphalt.com

 Factory
 : 259 Moo 8, Soi Ard.12032 Mittrapap Rd. Naklang Soongnern District, Nakhon Ratchasima 30380 Tel: +66 (0) 4433-5495-9 Fax: +66 (0) 4433-5495-9

 : 271 Moo 15 Phitsanulok-Bangragum Rd., Bangragum, Bangragum District Phitsanulok 65140 Tel: +66 (0) 5537-1461-2, 0-5537-1581-2 Fax: +66 (0) 5537-1461-2, 0-5537-1581-2 Ext. 360



Material Safety Data Sheet



(Premix)

- UEL %	Not applicable
Auto ignition Temperature	Not applicable
Chemical Reactivity	Not applicable
Materials to Avoid	Water
Hazardous Decomposition Products	Hydrocarbon

11. Toxicological Information	
Inhalation	It's not considered to be harmful by inhalation under normal
	use. Avoid vapors from heated materials in order not to
	absorb toxic mist which can irritate respiratory.
Skin Contact	Cause minor irritation, if contacted with materials which can
	damage inner skin layer.
• Ingestion	If victim is choking, it may cause chemical absorption into
	lung and will cause pneumonia.
Eyes Contact	Cause minor irritation, but it is extreme contacted may result
	in severe corneal injury and/or blindness.
• Chronic	Asphalt products contain low intensity level of polycyclic
	aromatic compound. It's not classified to be substances that
	are easily absorbed by the body and not carcinogenic.

12. Ecological Information	
Eco toxicity and Bioaccumulation	- Tend to accumulate in living organisms.
	- It's not expected to lower down the levels of ozone or to
	cause photochemical ozone creation / global warming.

13. Disposal Considerations

Wastes Disposal Instructions	- Able to be recycled by re-processing.
	- Assess its toxicity and physical appearance of wastes in
	order to re-classify types and disposal instructions in
	accordance with all applicable regulation.
	- Prohibit to dispose into waterways, sewers, basements /

 Head Office
 : Tipco Tower 118/1 Rama 6 Rd. Phayathai, Phayathai Bangkok10400 Tel: +66 (0) 2273-6000, 0-2271-0205 Fax: +66 (0) 2273-6030, 0-2271-1601 www.tipcoasphalt.com

 Factory
 : 259 Moo 8, Soi Ard.12032 Mittrapap Rd. Naklang Soongnern District, Nakhon Ratchasima 30380 Tel: +66 (0) 4433-5495-9 Fax: +66 (0) 4433-5495-9

: 271 Moo 15 Phitsanulok-Bangragum Rd., Bangragum, Bangragum District Phitsanulok 65140 Tel: +66 (0) 5537-1461-2, 0-5537-1581-2 Fax: +66 (0) 5537-1461-2, 0-5537-1581-2 Ext. 360



Material Safety Data Sheet



(Premix)

	confined areas or public water supply.
Container Disposal Instructions	- Dispose in accordance with all applicable regulations by
	certified collectors or subcontractors.
	- Should assess collectors / subcontractors qualification and
	capability before accessing permissible.
	- Dispose in accordance with local rules and regulations.
14. Transport Information	
Under the rules of UN, IMDG, IATA	It's not harmful in case transport at ambient temperature.
	It's not classified as hazardous materials.
15. Regulatory Information	
Governing Directive	Hazardous Substance Act B.E. 2535
16. Other Information	
16. Other Information Disclaimer	This MSDS was prepared in accordance with this specific
	This MSDS was prepared in accordance with this specific product based on manufacturer database and does not
	product based on manufacturer database and does not assume any liability arising out of product use with other
	product based on manufacturer database and does not
	product based on manufacturer database and does not assume any liability arising out of product use with other chemicals or other applications. The end user of the product
	product based on manufacturer database and does not assume any liability arising out of product use with other chemicals or other applications. The end user of the product has the responsibility for evaluating the adequacy of the
	product based on manufacturer database and does not assume any liability arising out of product use with other chemicals or other applications. The end user of the product has the responsibility for evaluating the adequacy of the data under these conditions of use, determining the safety,

Head Office : Tipco Tower 118/1 Rama 6 Rd. Phayathai, Phayathai Bangkok10400 Tel: +66 (0) 2273-6000, 0-2271-0205 Fax: +66 (0) 2273-6030, 0-2271-1601 www.tipcoasphalt.com

Factory

: 271 Moo 15 Phitsanulok-Bangragum Rd., Bangragum, Bangragum District Phitsanulok 65140 Tel: +66 (0) 5537-1461-2, 0-5537-1581-2 Fax: +66 (0) 5537-1461-2, 0-5537-1581-2 Ext. 360

: 61 Moo 5 Soi Suksawat Rd., Bangchak Phrapradaeng District Samutprakarn 10130 Tel: +66 (0) 2463-0169-70, 0-2817-5111-5 Fax: +66 (0) 2817-5117

: 259 Moo 8, Soi Ard.12032 Mittrapap Rd. Naklang Soongnern District, Nakhon Ratchasima 30380 Tel: +66 (0) 4433-5495-9 Fax: +66 (0) 4433-5495-9